

# Etrenzik LED Linear Tube Light

## "E" Series

### FEATURES ///

#### ENVIRONMENTALLY FRIENDLY, ENERGY EFFICIENT

- The Etrenzik LED "E" series delivers up to 3300 lumens while achieving up to 150 lumens per watt
- High efficiency retrofit conversion kit for T8 lamps in residential, commercial and industrial applications.
- Design Lights Consortium (DLC) qualified for acceptance in rebate, incentive and other programs nationwide
- Glass tube with shatter resistant sleeve
- UL-Damp and Dry Location
- NSF certified since May 20, 2016, date code 2216D
- Standard G13 bi-pin base for retrofit in any standard, non-shunted interior Tube fixture OR T5 Pins .



### PRODUCT SPECIFICATIONS ///

<b>Etrenzik E Series T8</b>	<b>12 - 25W - 4ft. / 9W - 2ft.</b>
<b>Power Data:</b>	<b>100 - 277VAC / Power Factor .98</b>
<b>Lumens:</b>	<b>1080-3300lms.</b>
<b>Lamp Base:</b>	<b>G13 Bi-pin / T5 Pin</b>
<b>CRI:</b>	<b>80</b>
<b>CCT:</b>	<b>4000K / 5000K</b>
<b>L70 Lifespan:</b>	<b>50,000hrs.</b>
<b>Beam Angle:</b>	<b>270°</b>
<b>Length / Diameter</b>	<b>47.24in - 1200mm / 1.02in - 26mm</b>
<b>Weight:</b>	<b>13oz. / 370g</b>
<b>Operation Temperature:</b>	<b>-13°F to + 113°F Ambient</b>
<b>Limited Warranty:</b>	<b>5 Years</b>
<b>Notes:</b>	UL-Damp and Dry Location - This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation. For FCC Part 15 user information, please see <a href="http://www.etrenzik.com">www.etrenzik.com</a>

#### PART NUMBER SPECIFICATION

For Example: ELT4-151Q505112

Family	Tube Length Ft.	Wattage		Voltage		Lumens		Color Temp		Lens		Power		Ended		Dimmable		
		9W	12W	120-277	1	1080	1800	4000K	5000K	Clear	Frosted	Internal	External	Single	Double	Dimmable	Non Dimmable	
ELT	2	9W	9	120-277	1	1080	F	4000K	40	Clear	1	Internal	1	Single	1	Dimmable	1	
	3	12W	12			1800	P	5000K	50	Frosted	5	External	2	Double	2	Non Dimmable	2	
	4	15W	15			1900	Q											
		18W	18			2200	R											

## CONTACT

Etrenzik Manufacturing, Inc.  
 (866) 267-7047 office • (678) 807-1900 Fax  
[Info@etrenzik.com](mailto:Info@etrenzik.com)

169 Creamer Drive  
 Alpharetta, GA 30004  
[www.etrenzikLED.com](http://www.etrenzikLED.com) / [www.etrenzik.com](http://www.etrenzik.com)